Sunlight Medical Assisted Reproduction Microtools



www.sunlightmedical.net

S unlight Medical Inc (SLM) manufactures and supplies a complete line of micropipettes for in vitro fertilization (IVF) procedures such as intracytoplasmic sperm injection (ICSI), embryo biopsy, assisted hatching, and other related procedures. We offer **consistency**, **precision**, **reliability**, **convenience**, **and value**.

Quality Assurance

SLM micropipettes are designed and manufactured under the direct supervision of scientists who are experts in the field of assisted reproduction technology (ART) and micromanipulation. Each micropipette is hand-crafted by highly trained technicians in a controlled environment and is individually examined for quality assurance.

SLM micropipettes are **traceable** to the materials, procedures, and production and QA personnel in preparing each individual pipette for **quality assurance**. This extra step puts pressure on everyone of us for consistent high quality products, but gives you relaxation and confidence for **precision manipulations and desired outcomes**.

Packaging

SLM pipettes are packed in our convenient **color coded** pipette safe cases. The case is designed with a **green** concept by using minimal materials for conservation and minimizing weight and size of the total package in the effort to reduce energy used for transportation. The outer box, including all labels, is made of paper for easy recycling.

Select an ICSI pipette that is best for your need!

Sunlight Medical offers three types of spiked ICSI injection pipettes for our diversified customers. The table below summarizes their differences, characteristics and advantages.

V type H type W type Characteristics: Characteristics: Characteristics: Short taper Longer taper Short taper Long parallel wall section Short parallel wall No parallel wall Tip to elbow length (0.55 mm Longer tip to elbow length Standard tip to elbow length or 1.00mm) (0.55 mm) $(0.75 \, \text{mm})$

ICSI Injection Pipettes

- SLM ICSI Injection Pipettes are used to perform intracytoplasmic sperm injection (ICSI).
- SLM offers three types of spiked and two types of non-spiked ICSI Injection Pipettes. See page 2 for details.
- All our injection pipettes are supplied with an angle of 0⁰ 45⁰ and a tip to elbow length of 0.55 mm and 1.0 mm.
- The flat tip ICSI pipette is for Piezo injection
- Other specifications and customized pipettes are available on request.



Catalogue Number	Size	Tip Style	Tip to Elbow Length	Tip Angle degree
SIC-45V-xx, SIC-45V-xxL SIC-45W-xx, SIC-45W-xxL SIC-45H-xx	ID: 4.0-4.5 μm OD: 5-6 μm	Spiked tip	xx – 0.55 mm xxL – 1.0 mm	
SIC-45T-xx, SIC-45T-xxL SIC-45N-xx, SIC-45N-xxL	ID: 4.0-4.5 μm OD: 5-6 μm	Non spiked tip	xx – 0.55 mm xxL – 1.0 mm	$xx - 0^{\circ}, 5^{\circ}, 10^{\circ}, 15^{\circ},$
SIC-50V-xx, SIC-50V-xxL SIC-50W-xx, SIC-50W-xxL SIC-50H-xx	ID: 4.5-5.0 μm OD: 6-7 μm	Spiked tip	xx – 0.55 mm xxL – 1.0 mm	20°, 25°, 30°, 35°, 40°, 45°
SIC-55V-xx, SIC-55V-xxL SIC-55W-xx, SIC-55W-xxL SIC-55H-xx	ID: 5.0-5.5 μm OD: 6-7 μm	Spiked tip	xx – 0.55 mm xxL – 1.0 mm	
SIC-45F-xxR SIC-50F-xxR	ID: 4.5-5.0 μm OD: 6-7 μm	Flat tip	xxR – 2.0 mm	




Holding Pipettes

- SLM Holding Pipettes are used to hold an oocyte or embryo in position during ICSI and other micromanipulation procedures.
- There are three series and six sizes for selection. The classic series has an ID 15-20 μm and OD in 90 μm , 100 μm , 120 μm , 130 μm and 150 μm . The 'S' series has smaller ID (10-15 μm). The 'B' series has an ID 25-30 μm and OD in 120 μm , 130 μm , 150 and 180 μm . The 'B' series may be used for holding an oocyte with cumulus cells attached and for embryo biopsy.
- All our holding pipettes are supplied with a tip angle of 0⁰ - 45⁰ and a tip to elbow length of 0.65 mm.
- Packed in a box of 10.

Catalogue Number	Outer Diameter μm	Inner Diameter μm	Tip Angle degree
SHP-70S-xx	70	10-15	
SHP-90-xx	90	15-20	
SHP-100-xx	100	15-20	
SHP-120-xx	120	15-20	
SHP-120B-xx	120	25-30	xx - 0°, 5°, 10°, 15°, 20°, 25°, 30°, 35°, 40°, 45°
SHP-130-xx	130	15-20	25°, 30°, 35°, 40°, 45°
SHP-130B-xx	130	25-30	
SHP-150-xx	150	15-20	
SHP-150B-xx	150	25-30	
SHP-180B-xx	180	25-30	

- SLM Blastomere Biopsy Pipettes are used to remove blastomeres and trophectoderm cells from embryos for pre-implantation genetic diagnosis (PGD).
- There are five sizes and two series available for selection. The 'Z' series is flat tip while the 'X' series is beveled tip. Both styles are supplied with an ID in 20 μm, 25 μm, 30 μm, 35 μm, and 40 μm. Size 20 μm and 25 μm are recommended for trophectoderm (TE) biopsy.
- There is no shrinkage at the bending section, so less likely to damage blastomere or loss of cells in case it is sucked through.
- All tips are fire polished to reduce damage to the cell membrane.
- They are supplied with a tip angle of 0⁰ 45⁰ and a tip to elbow length of 0.55 mm, 1.00 mm and 2.00 mm.

Blastomere Biopsy Pipettes



For trophectoderm (TE) biopsy use ID 20 μm and 25 μm pipettes.

Catalogue Number	Tip Style	Inner Diameter μm	Tip Angle degree	Tip to Elbow Length	
SBB-20Z-xx, xxR	Flat	20 ± 0.2			
SBB-25Z-xx, xxR	Flat	25 ± 0.2	$\mathbf{xx} - 0^{0}, \ 5^{0}, \ 10^{0}, \ 15^{0}, \ 20^{0}, \ 25^{0}, \ 30^{0}, \ 35^{0},$	xx – 0.55 mm	
SBB-30Z-xx, xxR	Flat	30 ± 0.2			
SBB-35Z-xx, xxR	Flat	35 ± 0.2	40°, 45°	xxL – 2.0 mm	
SBB-40Z-xx, xxR	Flat	40 ± 0.2			
SBB-20X-xx, xxR	Beveled	20 ± 0.2			
SBB-25X-xx, xxR	Beveled	25 ± 0.2	$\mathbf{xx} - 0^{\circ}, 5^{\circ}, 10^{\circ}, 15^{\circ}, 20^{\circ}, 25^{\circ}, 30^{\circ}, 35^{\circ},$	xx – 0.55 mm	
SBB-30X-xx, xxR	Beveled	30 ± 0.2			
SBB-35X-xx, xxR	Beveled	35 ± 0.2	40°, 45°	xxL – 2.0 mm	
SBB-40X-xx, xxR	Beveled	40 ± 0.2			

Pipette Controllers

LM 3-in-One Pipettor is a multi-actuated micro-pipette controller, which includes a hot sing and an access door, a ballonet seated at the housing. The ballonet is connected through a pipe to a pipe the pin base (ballonet assembly). The ballonet assembly can be replaced easily for contamination control. It can be operated in three ways:

- Pressing on the top cap for denudation of cumulus cells and gamete transfer.
- Press on the ballonet directly for denudation and transfer.
- Take the ballonet assembly out and use it like a Pasteur pipette.

Note: This product is for use in research only.



U.S. Patent approved

Polar Body Biopsy Pipettes



- SLM
 Polar Body Biopsy Pipettes are used to remove polar bodies from human oocytes and embryos for pre-implantation genetic diagnosis (PGD).
- There are three series of pipettes available for selection: 15Z (flat tip), 15X (beveled tip) and 15S (spiked tip).
- All these pipettes are designed with a fire polished edge to avoid damage to the cell membrane.
- They are supplied with a tip angle of 0⁰ 45⁰ and a tip to elbow length of 0.55 mm.

Catalogue Number	Inner Diameter µm	Tip Style	Tip Angle degree
SPB-15Z-xx	13-15	Flat	$xx - 0^0$, 5^0 , 10^0 , 15^0 , 20^0 ,
SPB-15X-xx	13-15	Beveled	25°, 30°, 35°, 40°,
SPB-15S-xx	13-15	Beveled and Spiked	45 ⁰

- SLM Denuding pipettes can be used with SLM 3in-One Pipette Controller and other pipette holders for denudation, and gametes and embryo transfer.
- The pipettes are made of borosilicate glass which is known for its stability, and is resistant to corrosion and remains absolutely neutral, even to aggressive chemicals in nearly all fields of chemistry.
- The glass pipette has better wetting feature comparing to plastic one, and is less likely to have oil drops attached inside which can sometimes damage an oocyte and embryo.
- Unpolished pipettes are used to remove cumulus cells attached to zona prior to micromanipulation procedures and fertilization assessment.

Denuding Pipettes



 Polished pipettes are used to transfer blastomere (during PGS), oocytes and embryos from one dish to another during other assisted reproduction procedures.

Catalogue Number	Inner Diameter µm	Tip Style	Catalogue Number	Inner Diameter µm	Tip Style
SDP-130	130-134	Unpolished	SDP-70P	65-74	Polished
SDP-140	135-144	Unpolished	SDP-80P	75-84	Polished
SDP-150	145-154	Unpolished	SDP-90P	85-99	Polished
SDP-160	155-164	Unpolished	SDP-100P	100-119	Polished
SDP-170	165-174	Unpolished	SDP-170P	170-189	Polished
			SDP-190P	190-219	Polished
			SDP-220P	220-249	Polished
			SDP-250P	250-289	Polished
			SDP-290P	290-319	Polished
			SDP-320P	320-360	Polished

PZD Pipettes



- SLM PZD Pipettes are used to cut an opening on the zona pellucida of an oocyte mechanically to enable assisted hatching and/or embryo biopsy.
- The pipette is designed with a very sharp tip and a strong taper section for easy control and precision manipulation.
- They are supplied with a 0^{0} 45^{0} tip angle and a tip to elbow length 0.55 mm.

Catalogue Number	Description	Tip Angle degree
SPD-30	Solid Sharp Tip	30

Instructions for Use:

- To open the case, hold the case as shown in Figure 1. Make sure that the "Sunlight" mark is up facing your right hand.
- Using your left index finger and thumb press the case on both sides marked "IIIII" then using your right index finger and thumb pull the top cover as shown in Figure 2.

Hold firmly the pipette in the middle and gently pull it out from the base as shown in Figure 3.













Caution: Consult accompanying document • Do not reuse • Sterilized using irradiation • Do not use if package is damaged • Store dry at room temperature • Keep away from Sunray







TF-004. L 2024--04-18

How to order?

please contact your local distributor when placing your order. If a distributor is not available in your region, orders can be placed by email: slm@sunlightmedical.net, fax: (904) 363 0958, or online at www.sunlightmedical.net.

We would be happy to send you samples for evaluation.

Visit us at www.sunlightmedical.net



Sunlight Medical, Inc.

5570 Florida Mining Boulevard S. Suite 603 Jacksonville, Florida 32257 U.S.A. slm@sunlightmedical.net

Phone: (904) 886 2900 / 866 7980

Fax: (904) 363 0958

ISO 13485

EC REP

AJW Technology Consulting GmbH Breite Straße 3 40213 Düsseldorf, Germany

